



**Char-Lynn**

**104-1774-006**

**Motors** - 2000 Series; Standard Mount Motor

**Model Code:** M02119AC15AA0100010AA0000AAAAF [Modify Configuration](#)

## Product Specifications

Feature	Code	Description
PRODUCT	M	MOTOR
SERIES	02	2000 SERIES
DISPLACEMENT	119	194.8 CM3/R [11.89 IN3/R]
MOUNTING TYPE	AC	STANDARD, 2 BOLT; 82.6 [3.25] PILOT DIA. 13.59 [.535] DIA. HOLES ON 106.4 [4.19] DIA. BOLT CIRCLE. SAE A
OUTPUT SHAFT	15	25.40 [1.000] DIA. STRAIGHT SHAFT WITH .250-20UNC-2B THREAD IN END, 6.35 [.250] WIDE X 25.40 [1.000] DIA. WOODRUFF KEY, CORROSION RESISTANT (SEAL AREA TO SHAFT END)
PORTS	AA	.875-14 UNF-2B SAE O-RING PORTS - STAGGERED PORTS
CASE FLOW OPTION	01	.4375-20 UNF-2B SAE O-RING PORT
LOW PRESSURE RELIEF	0	NONE
PRESSURE FLOW OPTION	00	NONE
GEROLER OPTION	1	STANDARD
SEAL OPTION	0	STANDARD
ACCESSORIES	AA	DIGITAL SPEED PICKUP (30 PULSE) 127 [5.0] LEAD WIRE WITH PACKARD WEATHER PAC SHROUD CONNECTOR (A=POWER, B=SIGNAL, C=COMMON)
SPECIAL FEATURES (HARDWARE)	00	NONE
SPECIAL FEATURES (ASSEMBLY)	00	NONE
PAINT/PACKAGING	AA	NO PAINT, INDIVIDUAL BOX
CUSTOMER IDENTIFICATION	AA	NONE
DESIGN CODE	F	SIXTH