

Interpump Plunger Pumps

47 Series Triplex - Male Shaft

- Flow rates up to 21 Lpm
- Pressures up to 275 Bar
- 1/2" BSP female inlet
- 3/8" BSP female outlet
- Brass manifold

Part No.	Bar	Lpm	HP	Rpm	Shaft OD	(LxWxH) mm	Kg
WS82	80	21	4	1450	24mm	298x224x146	14
WS92	90	18	4		24mm	298x224x146	14
WS101	100	15	4		24mm	298x224x146	14
WS102	100	21	5.5		24mm	321x224x146	14.5
WS132	120	18.7	5.5		24mm	321x234x146	14.5
WS151	150	15	5.5		24mm	321x234x146	14.5
WS162	160	18	7.5		24mm	321x234x146	14.5
WS171	170	13	5.5		24mm	321x234x146	14.5
WS201*	200	15	7.5		24mm	321x234x146	14.5
WS202*	200	21	10		24mm	321x234x146	14.5
WS251*	250	15	10		24mm	316x236x146	14.5
WS252*	250	21	14		24mm	316x236x146	14.5
W928*	275	12	10		24mm	316x236x146	14.5

*Nickel plated brass manifold



WS252, Nickel plated manifold

47 Series Triplex - Twin Male Shaft

- Flow rates up to 21 Lpm
- Pressures up to 200 Bar
- 1/2" BSP female inlet
- 3/8" BSP female outlet
- Brass manifold

Part No.	Bar	Lpm	HP	Rpm	Shaft OD	(LxWxH) mm	Kg
W151	150	15	5.5	1000	24mm	316x252x140	14.5
W162	160	18	7.5		24mm	316x252x140	14.5
W201*	200	15	7.5		24mm	316x252x140	14.5
WS151AA	150	15	5.5	1450	2 x 24mm	321x270x146	14.5
WS201AA*	200	15	7.5		2 x 24mm	321x270x146	14.5
WS202AA*	200	21	10		2 x 24mm	321x270x146	14.5

*Nickel plated brass manifold



63 Series Triplex - Male Shaft

- Flow rates up to 16 Lpm
- Pressures up to 200 Bar
- 1/2" BSP female inlet
- 3/8" BSP female outlet
- Brass manifold

Part No.	Bar	Lpm	HP	Rpm	Shaft OD	(LxWxH) mm	Kg
EL1411M	140	11	4.0	1450	24mm	213x211x122	8.05
EL1713M	170	13	5.8		24mm	213x211x122	8.05
EL1714M	170	14	6.2		24mm	213x211x122	8.05
EL2007M	200	7	3.7		24mm	213x211x122	8.15
EL2009M	200	9	4.7		24mm	213x211x122	8.15
EH1413M	140	13	4.8	2800	24mm	213x211x122	8.15
EH1416M	140	16	5.8		24mm	213x211x122	8.15
EH2011M	200	11	5.8		24mm	213x211x122	8.15



63 Series Triplex - Male Shaft - Unloader Valve with Chemical Injector

- Flow rates up to 16 Lpm
- Pressures up to 200 Bar
- 3/4" BSP male inlet
- 3/8" BSP male outlet
- Brass manifold

Part No.	Bar	Lpm	HP	Rpm	Shaft OD	(LxWxH) mm	Kg
EL1411MV	140	11	4.0	1450	24mm	285x211x207	8.25
EL1713MV	170	13	5.8		24mm	285x211x207	8.25
EL1714MV	170	14	6.2		24mm	285x211x207	8.25
EL2007MV	200	7	3.7		24mm	285x211x207	8.35
EL2009MV	200	9	4.7		24mm	285x211x207	8.35
EH1413MV	140	13	4.8	2800	24mm	285x211x207	8.35
EH1416MV	140	16	5.8		24mm	285x211x207	8.35
EH2011MV	200	11	5.8		24mm	285x211x207	8.35



When operating at temperatures above 40°C certain installation conditions must be observed, please contact our sales office for full details