

# ENSTO

## Tension clamp

SO85.2

---

Code SO85.2  
 GTIN 6418677405136  
 Name Tension clamp  
 Dia 6-14.9 mm (AAAC 25 - 150 mm<sup>2</sup>),  
 Suspension bolt D19 mm

Description For dead-ending bare and covered conductors. The covered conductor has to be peeled before installing the clamp. The body is made of corrosion resistant aluminium alloy and the bolts are hot dip galvanized steel. Breaking load >35 kN.



Vendor

## Technical specification

---

### Others

ETIM Class: EC003516

### Certificates

Standards: IEC 61284

### Features

Bolt: 2 x M12  
 For conductor size: AAAC 25-132, PAS 35-120, ACSR 25-99

### Mechanical

Breaking load: 35 kN  
 Max. continuous load: 20 kN  
 Tightening torque Nm: 55 Nm

### Dimensions

Conductor diameter: 6 ... 14.9 mm  
 Suspension bolt: 19 mm  
 Weight: 0.78 kg

## ETIM 7

---

### Etim

Type of accessory: Other

### Packaging

---

#### Pallet package

Unit: PCE  
Package size: 800  
Depth: 1200 mm  
Width: 800 mm

#### Default package

Unit: PCE  
Package size: 25  
Depth: 210 mm  
Width: 210 mm  
Height: 160 mm  
Volume: 7.056 l